§31.10-18a

using hammer test or such other means as may be necessary.

[CGFR 65-50, 30 FR 16662, Dec. 30, 1965, as amended by CGFR 68-32, 33 FR 5712, Apr. 12, 1968; CGD 84-044, 53 FR 7748, Mar. 10, 1988; USCG-1999-4976, 65 FR 6500, Feb. 9, 2000]

§ 31.10-18a Liquefied gas vessels: additional firefighting equipment inspections.

- (a) Once during each 12 month period after the month an original Certificate of Inspection is issued for a liquefied gas vessel under §31.05–1, the master shall ensure that the firefighting systems required in part 154 of this chapter for a liquefied gas vessel meets the following:
- (1) The exterior water spray system must past a water spray test.
- (2) The dry chemical system must meet the manufacturer's specifications for— $\,$
- (i) The amount of dry chemical powder: and
 - (ii) The pressure for nitrogen bottles.
- (3) The piping, valves, and controls of the system must be operable.
- (b) On the same date that the requirements under paragraph (a) of this section are met, the master shall record in the vessel's official logbook the following information:
 - (1) The date of the inspection.
- (2) The identification of each device inspected.
- (3) The name of the inspector.

[CGD 74-289, 44 FR 26006, May 3, 1979]

§31.10-19 All firefighting equipment may be tested—TB/ALL.

- (a) During the inspection of firefighting equipment, the Officer in Charge, Marine Inspection, may require fire apparatus to be tested, and used, except as provided under §§ 31.10– 18(h) and 34.15–90(a) of this subchapter.
 - (b) [Reserved]

§31.10-20 Definitions relating to hull examinations—T/B ALL.

As used in this part—

- (a) Drydock examination means hauling out of a vessel or placing a vessel in a drydock or slipway for an examination of all accessible parts of the vessel's underwater body and all throughhull fittings.
- (b) Internal structural examination means an examination of the vessel while afloat or in drydock and consists of a complete examination of the vessel's main strength members, including the major internal framing, the hull plating, voids, and ballast tanks, but not including cargo or fuel oil tanks.
- (c) Cargo tank internal examination means an examination of the vessel while afloat or in drydock and consists of an examination of the internals of all cargo tanks; except, if the vessel is certificated to carry cargoes regulated under part 38 or subchapter O of this chapter, the cargo tank internal examination must be accomplished as specified in parts 38 and 151 of this chapter respectively.
- (d) *Underwater survey* means the examination, while the vessel is afloat, of all accessible parts of the vessel's underwater body and all through-hull fittings.

[CGD 84-024, 52 FR 39649, Oct. 23, 1987, as amended by CGD 84-024, 53 FR 32229, Aug. 24, 1988; CGD 95-028, 62 FR 51197, Sept. 30, 1997]

§31.10-21 Drydock examination, internal structural examination, cargo tank internal examination, and underwater survey intervals—TB/ALL.

- (a) Except as provided in paragraphs (b) through (g) of this section, each tank vessel must undergo drydock, internal structural, and cargo tank internal examinations as follows:
- (1) Except under paragraph (a)(2) of this section, vessels that operate in salt water must be inspected in accordance with the intervals set forth in table 31.10–21(a). Where table 31.10–21(a) indicates a 2.5 year examination interval, it means a vessel must undergo two examinations within any five year period. No more than three years may elapse between any two examinations.